

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ :

H04Q 7/20, 7/32

A1

(11) International Publication Number:

WO 96/21327

(43) International Publication Date:

11 July 1996 (11.07.96)

(21) International Application Number: PCT/EP95/05077

(22) International Filing Date: 21 December 1995 (21.12.95)

(30) Priority Data:

P 9402693

30 December 1994 (30.12.94)

ES

(71) Applicant (for all designated States except AT BE CH CN DE DK ES FR GB GR IE IT LU MC NL PL PT RU SE US):
ALCATEL N.V. [NL/NL]; Burgemeester Elsenlaan 170,
NL-2288 BH Rijswijk (NL).

(71) Applicant (for all designated States except AU CA FI JP NZ US): ALCATEL STANDARD ELECTRICA S.A. [ES/ES];
Ramirez de Prado, 5/6, E-28045 Madrid (ES).

(72) Inventors; and

(75) Inventors/Applicants (for US only): GARCIA AGUILERA,
José Maria [ES/ES]; Islas Cies, 16, E-28035 Madrid (ES).
RODRIGO SANCHEZ, José Maria [ES/ES]; Ponzano, 91,
2.D, E-28003 Madrid (ES).

(74) Agents: KNECHT, Ulrich, Karl et al.; Alcatel SEL AG,
Zentralbereich Patente und Lizenzen, Postfach 300 929, D-
70449 Stuttgart (DE).

(81) Designated States: AU, CA, CN, FI, JP, NZ, PL, RU, US,
European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR,
IE, IT, LU, MC, NL, PT, SE).

Published


With international search report.

Before the expiration of the time limit for amending the
claims and to be republished in the event of the receipt of
amendments.

(54) Title: SUBSCRIBER IDENTITY AUTHENTICATION IN FIXED CELLULAR TERMINALS

(57) Abstract

The fixed cellular terminals (TCF) include a subscriber identity module which, in order to permit authentication of the identity of the subscriber (U) without any intervention on his part, is fixed. It is of particular application in fixed cellular terminals (TCF) of the GSM type that form part of an access network based on the infrastructure of a cellular mobile network. These subscriber identity modules incorporate the function of subscriber identification number verification. During the installation stage each fixed cellular terminal (TCF) stores the subscriber identification number, which it later provides to the subscriber identity module making it become fully active when the number supplied coincides with that held in the subscriber identity module. In the initialisation process, the fixed cellular terminal (TCF) generates a new subscriber identification number, that it stores internally in its subscriber identity module for use in subsequent reinitialisations.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Larvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

SUBSCRIBER IDENTITY AUTHENTICATION IN FIXED CELLULAR TERMINALS

FIELD OF APPLICATION

This invention refers to a procedure for subscriber identity authentication for fixed cellular terminals in radio access networks for fixed subscribers.

This procedure is of special application in fixed cellular terminals of the GSM type that form part of an access network for fixed subscribers, implemented making use of the infrastructure of a cellular mobile network, permitting authentication of subscriber identity without any intervention being required on the part of the fixed subscribers in question.

BACKGROUND OF THE INVENTION

The use of mobile cellular terminals with "fixed mobility" for access to two-wire fixed subscriber networks is very suitable for those situations where the major investment required for the installation of a wired access network is not justified because, for example, of a low subscriber density. These subscribers therefore, make use of mobile cellular technology in the fixed access network, but tariffication of their calls is the same as that of those subscribers with wired access networks.

The fixed cellular terminals have their own design, since they are not equipped with the proper mobility functions (handover, roaming, etc.), for which they have no need. On the other hand, however, they have to support new features that are not required in true mobile cellular terminals (for example, the subscriber side two-wire interface function).

Depending on the type, the cellular terminals, whether or not they have fixed mobility, can include a module in which reside the functions required for subscriber identity authentication, for which they make use of subscriber identification numbers that are allocated to the subscribers in such a way that each number identifies a single subscriber. This module, for the case of cellular terminals with GSM technology, is known as the Subscriber Identity Module, or SIM. In the case of mobile cellular terminals, this module takes the form of a board that can be removed from the terminal; while in the case of cellular terminals with fixed mobility, this module is internal and built into the terminals in such a way that the subscriber is completely detached from how he accesses the main network

using cellular technology, since access is obtained in the same way as that of a subscriber to a wired access network.

The European standard ETS 300 509 "European Digital Cellular Telecommunication System (phase 2); Subscriber Identity Modules (SIM) Functional Characteristics (GSM 02.17)", September 1994, developed by the
5 Technical Committee SMG (Special Mobile Group) of the ETSI, defines the functional characteristics of this subscriber identity module (SIM) for use in GSM applications.

On page 12 of the document mentioned, and within the section
10 concerning security aspects, reference is made to the presence of this subscriber identity module SIM with the verification function of the subscriber identification number. When this function is enabled, the subscriber identity module SIM, to become fully activated and thereby to permit access to all its functions, first requires the insertion of the subscriber
15 identification number and that this number coincide with the subscriber identification number which has been stored in it during manufacture.

This function facilitates protection against the use of other subscriber identity modules SIM or of cellular terminals that incorporate them, by others apart from authorised persons. On the other hand, the enabling of
20 this function in fixed cellular terminals that form part of an access network for two-wire subscribers, would result in an inconvenience for them, since, in some manner, they would have to introduce from their terminal their subscriber identification number each time they make a call.

The European standard mentioned permits the inhibition of this
25 function; consequently it is disabled when cellular terminals with fixed mobility are used as integral parts of wired networks, in order to avoid inconvenience to subscribers. However with this, there is still the potential risk that these modules with the function in question disabled, could be removed from the fixed cellular terminals and used, for example, in mobile
30 cellular terminals since they have no need for introducing any subscriber identification number to make calls, these calls moreover being charged at wired network rates.

As a consequence of the foregoing, the technical problem to be overcome lies in how to ensure that the use of cellular terminals with fixed
35 mobility as integral parts of access networks does not impair the security

functions incorporated in these terminals, without this involving any inconvenience or complication for subscribers when making calls, there being complete transparency for a subscriber with a fixed mobility cellular terminal.

5 CHARACTERISATION OF THE INVENTION

This invention presents a procedure for subscriber identity authentication for fixed cellular terminals, through the use of subscriber identification numbers. To implement the procedure in question, the subscriber identity module has the verification function of the subscriber
10 identification number enabled.

The procedure consists in that, during the installation process, each fixed cellular terminal has the subscriber identification number stored in it, which it subsequently transmits to its particular subscriber identity module permitting this module to become fully activated if the number supplied
15 coincides with that stored internally in the module.

When initialising the equipment, each fixed cellular terminal generates a new subscriber identification number, which it stores in the terminal itself and in its corresponding subscriber identity module. The new subscriber identification number activates the subscriber identity
20 module in later reinitialisations.

The advantages of using this procedure are that, making use of mobile cellular technology, it permits the use of fixed cellular terminals with all their security functions enabled in order to provide access to a wired network for a group of fixed subscribers, in those cases where it is
25 not economically or technically feasible to implement a wired access network. In this way, subscriber identity authentication is performed, avoiding the possibility of fraudulent use but without causing any inconvenience to the fixed subscribers, since the later have no need to intervene in any way and therefore have access to the telephone service in
30 identical manner that subscribers to wired networks.

BRIEF FOOTNOTES TO THE FIGURES

A fuller explanation of the invention can be obtained from the following description of a preferred implementation based on the figures attached, in which:

35 - figure 1 shows access by subscribers terminals to a wired network

by means of a mobile network incorporating fixed cellular terminals in which the subscriber identity authentication procedure object of this invention has been implemented, and

- figure 2 shows a functional block diagram of a fixed cellular terminal, which implements the subscriber identity authentication procedure object of this invention.

DESCRIPTION OF A PREFERRED IMPLEMENTATION

The drawing of figure 1 shows a fixed subscriber access communications system implemented by taking advantage of an already established mobile communications infrastructure.

This system incorporates a mobile cellular communications network formed by a mobile switching centre CCM that permits access to a wired network RF and by a set of base stations BS, connected to this mobile switching centre CCM. Each base station BS provides coverage for a determined zone in which there are cellular mobile terminals TCM as well as fixed cellular terminals TCF. In the latter, the subscriber identity authentication procedure of this invention has been implemented. These fixed cellular terminals TCF offer a standard access interface to the wired network RF for a set of fixed subscriber terminals U.

The cellular technology employed in this implementation uses the European standard GSM (Global System for Mobile), developed by the ETSI (European Telecommunications Standards Institute), for standardisation of digital cellular mobile telephony on an European level.

As it is illustrated in figure 2, in each fixed cellular terminal TCF the following functional modules can be identified:

- a low frequency signals and control module BFC, for managing audio channels and other control processes;
- a radio module RAD, that performs the functions of transmitting and receiving, by radio, the signals that are interchanged between the fixed cellular terminal TCF itself and the base stations BS;
- an interface module Z in which are grouped together the two-wire subscriber line interface functions;
- a subscriber identity module SIM in which reside the functions that carry out the identity authentication of the subscriber U.

Initially, each subscriber identity module SIM leaves the factory with

a subscriber identification number stored in it, and this is known to the operator.

One of the functions directed at the authentication of the subscriber identity above mentioned is the verification function of the subscriber identification number. In the event that it is enabled, for the subscriber identity module SIM to become fully activated and permit access to all the functions resident in it, it is first necessary to provide it with the subscriber identification number.

At this point the subscriber identity module SIM compares the subscriber identification number that it has been provided with, with that which was previously stored, in such a way that the subscriber identity module SIM only permits access to the rest of its functions if the result of the comparison process reveals both numbers to be identical.

In the preferred implementation described below, the subscriber identity module SIM of each fixed cellular terminal TCF is fixed and built-in, and, in contrast with what occurs in the other fixed cellular terminals, it has the verification function of the subscriber identification number enabled, so that initially the subscriber identity module SIM is not fully activated.

At the installation stage of the fixed cellular terminals TCF, the operator inserts in each fixed cellular terminal TCF, from its respective subscriber terminal U, the subscriber identification number that was stored during manufacture in the subscriber identity module SIM corresponding to that fixed cellular terminal TCF. Each fixed cellular terminal TCF stores this number internally in an EEPROM.

The fixed cellular terminal TCF then carries out the complete activation of its subscriber identity module SIM in order to gain full access to all its functions. To this end, and since the subscriber identity module SIM has the verification function of the subscriber identification number enabled, the fixed cellular terminal TCF supplies it with the subscriber identification number previously stored in the EEPROM. The subscriber identity module SIM compares this number that is supplied by the fixed cellular terminal TCF with that which it already had stored in it during manufacture. The result of this comparison is that both numbers coincide, whereby the subscriber identity module SIM becomes fully activated and

therefore permits access to all its functions and, for this to happen, there is no requirement for intervention on the part of the subscribers U.

Prior to normal operation, and during the initialisation process, the fixed cellular terminal TCF generates a new subscriber identification number, it being recorded in a buffer memory of the low frequency signals and control module BFC that the installation stage has been completed, in order to indicate this later.

In order to generate the new subscriber identification number, the fixed cellular terminal TCF performs a series of arithmetical functions, such as those described below by way of example:

The fixed cellular terminal TCF takes as input data the subscriber identification number that it has stored in the EEPROM. Following this, it determines the number of digits that constitute this number, and which can vary between four and eight digits. Depending on the result, it adds a number of zeros until an eight-digit number is obtained. Finally the fixed cellular terminal TCF inverts the odd and even positions of this last number and thereby produces the new subscriber identification number.

Once the fixed cellular terminal TCF has generated the new subscriber identification number, it is also stored in its low frequency signals and control module BFC.

Subsequently it transmits this new subscriber identification number to the subscriber identity module SIM, in which it is also stored for use later in normal operation of the fixed cellular terminal TCF, replacing that which was previously there. The fixed cellular terminal TCF has to employ this new subscriber identification number each time it requires access to the functions of the subscriber identity module SIM, in the event that the latter is inhibited and has to be enabled again (for example, after housekeeping operations, in which it is not necessary to maintain the subscriber identity module activated).

In this way the fixed cellular terminal TCF fully activates the subscriber identity module SIM, without any intervention on the part of the subscriber U being necessary and, on the other hand, the subscriber identification number stored in each subscriber identity module SIM is changed, this number being now unknown to either the subscriber or the operator of the system, thereby preventing use of the subscriber identity

modules SIM outside their respective fixed cellular terminal TCF since, in the event of being removed from their corresponding fixed cellular terminal TCF, it will be necessary to insert the new subscriber identification number in order to re-enable them, but this number is unknown to all parties.

CLAIMS

1.- PROCEDURE FOR AUTHENTICATION OF SUBSCRIBER IDENTITY for fixed cellular terminals (TCF), implemented by a subscriber identity module (SIM) incorporated in these fixed cellular terminals (TCF) by making use of a subscriber identification number, characterised in that each fixed cellular terminal (TCF):

- stores the subscriber identification number,
- supplies the subscriber identity module (SIM) with this subscriber identification number, and
- 10 - fully activates the subscriber identity module (SIM) in the event that the number supplied coincides with that stored internally in the subscriber identity module (SIM).

2.- PROCEDURE FOR AUTHENTICATION OF SUBSCRIBER IDENTITY according to claim 1, characterised in that these functions are implemented when installing the actual fixed cellular terminal (TCF).

3.- PROCEDURE FOR AUTHENTICATION OF SUBSCRIBER IDENTITY according to claim 1, characterised in that in addition each fixed cellular terminal (TCF) generates a new subscriber identification number and stores this new subscriber identification number in both an internal memory and in the subscriber identity module (SIM).

4.- PROCEDURE FOR AUTHENTICATION OF SUBSCRIBER IDENTITY according to claim 3, characterised in that these functions are implemented during the initialisation of the fixed cellular terminal (TCF).

5.- FIXED CELLULAR TERMINAL (TCF) for use in access systems with mobile cellular technology for access by a set of subscribers (U) to a fixed network (RF), which comprises a subscriber identity module (SIM) that performs the subscriber identity authentication; this fixed cellular terminal (TCF) being characterised in that the subscriber identity module (SIM) has the verification function of the subscriber identification number enabled within the subscriber identity authentication process.

6.- FIXED CELLULAR TERMINAL (TCF) according to claim 5, characterised in that it includes:

- means to store the subscriber identification number;
- means to supply the subscriber identity module (SIM) with the subscriber identification number and thereby activate it fully in the event

that the number supplied coincides with that stored internally in the subscriber identity module (SIM),

- means to generate a new subscriber identification number,
 - means to store the new subscriber identification number in both an
- 5 internal memory and in its subscriber identity module (SIM).

7.- **FIXED CELLULAR TERMINAL (TCF)** according to claim 6, characterised in that when it is reinitialised, it employs the new subscriber identification number in order to verify the authenticity of the identity of the subscriber (U).





FIG. 1

**FIG. 2**

INTERNATIONAL SEARCH REPORT

national Application No

EP 95/05077

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 H04Q7/20 H04Q7/32

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE,U,92 17 379 (TELEFONAKTIEBOLAGET L M ERICSSON) 29 April 1993 see page 4, line 36 - page 5, line 6 see page 6, line 11 - line 22 ---	1,5
A	EP,A,0 301 740 (NOKIA MOBIRA OY) 1 February 1989 see column 3, line 15 - column 4, line 16 -----	1,5

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

10 May 1996

Date of mailing of the international search report

15.05.96

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.
Fax (-31-70) 340-3016

Authorized officer

Gerling, J.C.J.

INTERNATIONAL SEARCH REPORT

Information on patent family members

tional Application No

PAT/EP 95/05077

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE-U-9217379	29-04-93	SE-B- 470519	27-06-94
		AU-B- 5049893	19-05-94
		BR-A- 9394655	14-06-94
		CA-A- 2102391	10-05-94
		CN-A- 1091877	07-09-94
		EP-A- 0607767	27-07-94
		FI-A- 934924	10-05-94
		JP-A- 6216842	05-08-94
		SE-A- 9203351	10-05-94
<hr/>			
EP-A-0301740	01-02-89	AT-T- 106645	15-06-94
		DE-D- 3889800	07-07-94
		DE-T- 3889800	09-03-95
		DK-B- 169158	29-08-94
		JP-A- 1106533	24-04-89
		NO-C- 173679	12-01-94
		US-A- 4868846	19-09-89
<hr/>			